


CAPRI R 2 P

- Round hanging fixture.
- Prismatic PS diffuser.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- Supplied with steel hanging cables (adjustable 2.00m max), black or white round base and power cable.
- Phase break dimmable or DALI-push dimmable converter built in the device.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
SU15405	MATT BLACK	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	2910 Lm (4000K)
SU15430	MATT WHITE	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	2910 Lm (4000K)
SU15405DA	MATT BLACK	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	2910 Lm (4000K)
SU15430DA	MATT WHITE	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	2910 Lm (4000K)



MATT BLACK



MATT WHITE



Suspended mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Beam 90°.



Product in conformity CE.



CRI>90



3 CCT.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Power supply included.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.