


CAPRI R 3 C

- Wall or ceiling lamp.
- Prismatic PS diffuser.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- DALI dimmable converter included in the profile.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA21805DA	MATT BLACK	ALUMINIUM	AC 230V	105W	2700-3000-4000K	11800 Lm (4000K)	7070 Lm (4000K)
WA21830DA	MATT WHITE	ALUMINIUM	AC 230V	105W	2700-3000-4000K	11800 Lm (4000K)	7070 Lm (4000K)



MATT BLACK



MATT WHITE

ACCESSOIRES	DESCRIPTION	L (mm)
-------------	-------------	--------

CD127	DALI PCU LIGHTING MANAGEMENT	48
-------	------------------------------	----



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Beam 90°.



Product in conformity CE.



CRI > 90



3 CCT.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Power supply included.




The product is dimmable (DALI input).




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.