



# CAPRI S 2 C

- Wall or ceiling lamp.
- PS diffuser with prismatic structure.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- Dimmable phase cut or dimmable DALI-push converter built in the device.



This product contains 1 light source(s) of energy efficiency F.


















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA24305	MATT BLACK	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	3175 Lm (4000K)
WA24330	MATT WHITE	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	3175 Lm (4000K)
WA24305DA	MATT BLACK	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	3175 Lm (4000K)
WA24330DA	MATT WHITE	ALUMINIUM	AC 230V	42W	2700-3000-4000K	5150 Lm (4000K)	3175 Lm (4000K)




MATT BLACK




MATT WHITE

-  Wall and ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 90°.
-  Product in conformity CE.
-  CRI>90
-  3 CCT.  
2700K  
3000K  
4000K
-  LED specifications.  
L80B20  
50,000h
-  UGR below 19.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  The product is dimmable.
-  5 years warranty.
-  Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.