


# CLAC 1 MINI

- Adjustable round wall or ceiling lamp.
- Dimmable converter built in in the device.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.




















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA182SW05	MATT BLACK	ALUMINIUM	AC 230V	8W	2700K	710 Lm	435 Lm
WA182SW30	MATT WHITE	ALUMINIUM	AC 230V	8W	2700K	710 Lm	435 Lm
WA182WW05	MATT BLACK	ALUMINIUM	AC 230V	8W	3000K	750 Lm	467 Lm
WA182WW30	MATT WHITE	ALUMINIUM	AC 230V	8W	3000K	750 Lm	467 Lm



MATT BLACK




MATT WHITE


-  Wall and ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 355°.
-  Beam 38°.
-  Product in conformity CE.
-  CRI>90
-  LED specifications.
-  UGR below 19.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  The product is dimmable.
-  3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.