


# CURLI 1 RD

- Fixed down recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- Optional dimmable converter DALI CD123 to be ordered separately.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO287WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1050 Lm	789 Lm
DO287NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	4000K	1140 Lm	870 Lm

ACCESSOIRES	COLOR	DESCRIPTION
DO42030	MATT WHITE	CURLI 1 RD SQUARE FRAME 85X85mm



CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD123	3-18W	AC 230V	DC 250mA	1	1	80°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (70mm)



Beam 40°.



Product in conformity CE.



CRI>80



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.





Connect to a constant current Led power supply of 250mA DC.




The product is dimmable.

**5** 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.