


# CURLI 2 RD

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- As an option, DALI CD140 dimmable converter to be ordered separately.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO288WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 37V	15W	3000K	1520 Lm	1215 Lm
DO288NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 37V	15W	4000K	1580 Lm	1224 Lm

ACCESSOIRES	COLOR	DESCRIPTION
DO42130	MATT WHITE	CURLI 2 RD SQUARE FRAME 105x105mm



CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD140	3-18W	AC 230V	DC 350mA	1	1	80°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (85mm)



Beam 40°.



Product in conformity CE.



CRI >80



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.





Connect to a constant current Led power supply of 350mA DC.




The product is dimmable.

**5** 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.