


CURLI 3 RD

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- As an option, DALI CD126 dimmable converter to be ordered separately.

This product contains 1 light source(s) of energy efficiency F(3000K), E(4000K).



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO289WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 37V	25W	3000K	2450 Lm	1934 Lm
DO289NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 37V	25W	4000K	2580 Lm	2181 Lm

ACCESSOIRES	COLOR	DESCRIPTION
DO42230	MATT WHITE	CURLI 3 RD SQUARE FRAME 145x145mm



CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD126	4-27W	AC 230V	DC 500mA	1	1	85°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire. (120mm)



Beam 40°.



Product in conformity CE.



CRI>80



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.





Connect to a constant current Led power supply of 500mA DC.




The product is dimmable.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.