



CURTIS PLUS

















- Spotlight for outdoor lighting.
- 3000K, 4000K or 5000K as desired via a switch at the back of the luminaire.
- Polycarbonate diffuser.
- Supplied with 0.50m cable.
- Non-dimmable converter built in the device.



This product contains 1 light source(s) of energy efficiency E (4000K), F (3000K-5000K).


CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)	H (mm)
OU47024	ANTHRACITE	CAST ALUMINIUM	AC 230V	15W	3000-4000-5000K	1700 Lm (4000K)	1340 Lm (4000K)	147	123
OU47124	ANTHRACITE	CAST ALUMINIUM	AC 230V	30W	3000-4000-5000K	3500 Lm (4000K)	2910 Lm (4000K)	178	148
OU47224	ANTHRACITE	CAST ALUMINIUM	AC 230V	50W	3000-4000-5000K	5850 Lm (4000K)	4225 Lm (4000K)	208	170
OU47324	ANTHRACITE	CAST ALUMINIUM	AC 230V	70W	3000-4000-5000K	8000 Lm (4000K)	6435 Lm (4000K)	260	189

ACCESSOIRES	DESCRIPTION	
OU48405	CONNECTOR 2PIN IP68	
OU48505	CONNECTOR 3PIN IP68	


-  Wall mounting only.
-  Ground mounting only.
-  Outdoor use.
-  Protected against the ingress of dust. Protected against jets of water.
-  Protection against an impact energy of 20 Joules.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 180°.
-  Beam 120°.
-  Product in conformity CE.
-  CRI >80
-  3 CCT.
3000 K
4000 K
5000 K
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable control gear.



Non-replaceable light source.