


CURTIS SENSOR PLUS

- Spotlight for outdoor lighting.
- 3000K, 4000K or 5000K as desired via a switch at the back of the luminaire.
- Polycarbonate diffuser.
- Supplied with 0.50m cable.
- With 120° IR adjustable sensor, adjustable detection area to max. 8m.
- Non-dimmable converter built in the device.



This product contains 1 light source(s) of energy efficiency E (4000K), F (3000K-5000K).

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)	H (mm)
OU47424	ANTHRACITE	CAST ALUMINIUM	AC 230V	15W	3000-4000-5000K	1700 Lm (4000K)	1340 Lm (4000K)	147	175
OU47524	ANTHRACITE	CAST ALUMINIUM	AC 230V	30W	3000-4000-5000K	3500 Lm (4000K)	2910 Lm (4000K)	178	201
OU47624	ANTHRACITE	CAST ALUMINIUM	AC 230V	50W	3000-4000-5000K	5850 Lm (4000K)	4225 Lm (4000K)	208	223

ACCESSOIRES	DESCRIPTION	
OU48405	CONNECTOR 2PIN IP68	
OU48505	CONNECTOR 3PIN IP68	



Wall mounting only.



Outdoor use.



Protected against dust, And protected against water spray.



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 180°.



Beam 120°.



Product in conformity CE.



CRI>80



3 CCT.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




With sensor.




3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable control gear.



Non-replaceable light source.