

# CYCLO SENSOR

- Round terminal for outdoor lighting.
- Polycarbonate.
- With 90° IR sensor, detection area ajustable to max 5 m.
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
OU516WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	24W	3000K	2100 Lm	1660 Lm	600
OU391WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	24W	3000K	2100 Lm	1660 Lm	955

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
OU39224	ANTHRACITE	CAST ALUMINIUM	REFLECTOR 180°



Floor mounting only.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




With sensor.



5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.