
## **DOWNLIGHTS**



## **DAX RD-230**





- 4 in 1 fixed round recessed downlight.
- 2700K, 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire .
- Fastened with springs.
- Can be covered by peeled or blown insulation.
- Automatic double terminal block.
- Does not require a converter.
- Dimmable.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO48730	MATT WHITE	COMPOSITE	AC 230V	6W	2700-3000-4000-6000K	850 Lm (4000K)	676 Lm (4000K)





Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double



Hole cut to insert luminaire (68mm)



Beam 100°.





Product in conformity CE.



CRI>80





Photobiological risk RG0



LED LED specifications.



In compliance with current thermal regulation. (France) RE



Test on 850°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Luminaire with a 230V LED module.



The product is dimmable.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable light source.