


# DEAN RDX PLUS

- 3 in 1 adjustable round semi-recessed spotlight.
- 2700K, 3000K or 4000K as desired via a Switch on the converter.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO52605	MATT BLACK	ALUMINIUM	AC 230V	DC 700mA 36V	28W	2700-3000-4000K	2300 Lm (4000K)	1625 Lm (4000K)
DO52630	MATT WHITE	ALUMINIUM	AC 230V	DC 700mA 36V	28W	2700-3000-4000K	2300 Lm (4000K)	1625 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire. (80mm)



Minimum ceiling height to insert luminaire. (50mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 355°.



Beam 38°.



3 CCT.



Product in conformity CE.



CRI > 90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 700mA DC.




The product is dimmable.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.