


# DEBI RD-230

RE  
2020



- 4 in 1 fixed round recessed spotlight.
- 2700K, 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Can be covered by peeled or blown insulation.
- Automatic double terminal block.
- Does not require a converter.
- Dimmable.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.

| CODE    | COLOR      | MATERIAL       | AC      | LED | T° (K)               | LED Lumen      | System Lumen   |
|---------|------------|----------------|---------|-----|----------------------|----------------|----------------|
| DO44505 | MATT BLACK | ALU.+COMPOSITE | AC 230V | 5W  | 2700-3000-4000-6000K | 620 Lm (4000K) | 506 Lm (4000K) |
| DO44530 | MATT WHITE | ALU.+COMPOSITE | AC 230V | 5W  | 2700-3000-4000-6000K | 620 Lm (4000K) | 506 Lm (4000K) |



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



Beam 60°.



Product in conformity CE.



CRI>80



4 CCT.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 850°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)




Luminaire with a 230V LED module.




The product is dimmable.



**3** 3 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable LED light source by an electrician.