


DEBI RD

RE
2020



- 4 in 1 fixed round recessed spotlight.
- 2700K, 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Can be covered by peeled or blown insulatiion, converter included.
- Automatic double terminal block.
- Remote dimmable converter supplied.
- Compatible with end-of-phase dimmer.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO43005	MATT BLACK	ALU.+COMPOSITE	AC 230V	DC 200mA 27V	6W	2700-3000-4000-6000K	720 Lm (4000K)	570 Lm (4000K)
DO43030	MATT WHITE	ALU.+COMPOSITE	AC 230V	DC 200mA 27V	6W	2700-3000-4000-6000K	720 Lm (4000K)	570 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (65mm)



Beam 60°.



Product in conformity CE.



CRI>80



4 CCT.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Class II power supply included.



200
mA

Connect to a constant current Led power supply of 200mA DC.




The product is dimmable.

3


3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.