TECHNICAL DATA **OUTDOOR** WALL RECESSED LIGHTS



DEVI

CODE

- Rectangular outdoor recessed beacon wall light.

- Recessed box supplied.
- With cable inlet and outlet.
- Non dimmable converter built in the device.

COLOR

This product contains 1 light source(s) of energy efficiency C.

MATERIAL



T° (K)



System Lumen

87

LED Lumen

					- ()		0,000 -0.000
OU350NW24	ANTHRACITE	ALUMINIUM	AC 230V	8,5W	4000K	500 Lm	189 Lm
Recessed	I wall mounting only.						
Indoor an	d outdoor use.						
IP 65 Protected	against the ingress	of dust. Protected against	jets of water.				
IK 05 Protection	n against an impact e	energy of 0,70 Joule.					
Earth wire	e. Fixture equipped v	with primary insulation only	ν.				
Rectangu	lar piercing to insert	the luminaire. (240x74mm)				
	o conformity CE.						
CRI 280							
LED LED spec	ifications.						
	ogical risk RG1						
650° Test on 6	50°.						
Power su	oply included.						
3 years w	arranty.						
	ric data available on	our website: www.indigo-l	ighting.com				
F	eplaceable LED ligh	t source by an electrician.					

AC

LED



Replaceable control gear by an electrician.