


DLK2072 RX GU10

- Adjustable round recessed spotlight.
- 3 crowns.
- Fastened with springs.





CODE	COLOR	MATERIAL	SOCKET	AC	Watt Max	LAMP
DLK207204	WHITE	CAST ALUMINIUM	GU10	AC 230V	50W	PAR16
DLK207215	BRUSHED STAINLESS STEEL	CAST ALUMINIUM	GU10	AC 230V	50W	PAR16
DLK207221	SATIN NICKEL	CAST ALUMINIUM	GU10	AC 230V	50W	PAR16





WHITE

BRUSHED STAINLESS SATIN NICKEL STEEL

Ā	Recessed ceiling mounting only.
	Indoor use only.
IP 23	Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.
IK 06	Protection against an impact energy of 1 Joule.
	Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
6 82	Hole cut to insert luminaire (82 mm)
7 30°	The luminaire can be adjusted vertically up to a maximum of 30°.
⊖ 355°	Horizontal orientation maximum to 355°.
CE	Product in conformity CE.
650°	Test on 650°.
	Product can not be covered after installation even with insulation.
2	2 years warranty.



Replaceable light source by an end-user.