


DOMINO CSP

This product contains 16 light source(s) of energy efficiency C.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	System Lumen
DMB66N4K	BLACK	STEEL	AC 230V	DC 600mA	22W	4000K	3550 Lm
				DC 650mA	24W		3850 Lm
				DC 700mA	25W		4100 Lm
				DC 750mA	27W		4350 Lm
DMW66N4K	WHITE	STEEL	AC 230V	DC 600mA	22W	4000K	3550 Lm
				DC 650mA	24W		3850 Lm
				DC 700mA	25W		4100 Lm
				DC 750mA	27W		4350 Lm



BLACK



WHITE

ACCESSOIRES	DESCRIPTION	L (mm)
LEDEP10	EMERGENCY CONVERTER	200



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. No protection against the ingress of liquids.



Protection against an impact energy of 5 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Beam 75°.



Product in conformity CE.



Colour rendering index >80.



UGR below 16.



Photobiological risk RG0



Product can not be covered after installation even with insulation.



Power supply included.



5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.