


DOTS C

- Fixed rectangular ceiling lamp for accent lighting.
- Dimmable converter built in in the device.
- Compatible with start and end phase dimmer.

This product contains 3(6W), 6(12W), 9(18W) energy efficiency G.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
WA248WW05	MATT BLACK	ALUMINIUM	AC 230V	6W	3000K	470 Lm	300 Lm	108
WA248WW30	MATT WHITE	ALUMINIUM	AC 230V	6W	3000K	470 Lm	300 Lm	108
WA249WW05	MATT BLACK	ALUMINIUM	AC 230V	12W	3000K	940 Lm	565 Lm	188
WA249WW30	MATT WHITE	ALUMINIUM	AC 230V	12W	3000K	940 Lm	565 Lm	188
WA250WW05	MATT BLACK	ALUMINIUM	AC 230V	16W	3000K	1400 Lm	895 Lm	268
WA250WW30	MATT WHITE	ALUMINIUM	AC 230V	16W	3000K	1400 Lm	895 Lm	268
WA251WW05	MATT BLACK	ALUMINIUM	AC 230V	20W	3000K	1880 Lm	1165 Lm	348
WA251WW30	MATT WHITE	ALUMINIUM	AC 230V	20W	3000K	1880 Lm	1165 Lm	348





MATT BLACK


MATT WHITE


MATT BLACK


MATT WHITE

 Ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 0,70 Joule.


 Live parts are equipped with additional isolation protection, such as reinforced or double insulation.


 Beam 45°.


 Product in conformity CE.


 CRI>80


 LED specifications.


 UGR below 19.

 Photobiological risk RG1

 Test on 650°.

 Power supply included.


 The product is dimmable.

 5 years warranty.






Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.