


DOTS

- Recessed spotlight for accent lighting.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- DO497, DO49 and DO499 in DALI version: converter with push-dim function.



This product contains 1(3W), 3(6W), 6(12W) energy efficiency G.

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
PHASE CUT DIMMABLE									
DO500WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 6V	3W	3000K	320 Lm	148 Lm	48
DO500WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 6V	3W	3000K	320 Lm	148 Lm	48
DO496WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 9V	6W	3000K	470 Lm	345 Lm	102
DO496WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 9V	6W	3000K	470 Lm	345 Lm	102
DO497WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 18V	12W	3000K	940 Lm	609 Lm	182
DO497WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 18V	12W	3000K	940 Lm	609 Lm	182
DO498WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 27V	16W	3000K	1400 Lm	1011 Lm	262
DO498WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 27V	16W	3000K	1400 Lm	1011 Lm	262
DO499WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 36V	20W	3000K	1880 Lm	1217 Lm	342
DO499WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 36V	20W	3000K	1880 Lm	1217 Lm	342
DALI DIMMABLE									
DO500WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 6V	3W	3000K	320 Lm	148 Lm	48
DO500WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 6V	3W	3000K	320 Lm	148 Lm	48
DO496WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 9V	6W	3000K	470 Lm	345 Lm	102
DO496WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 9V	6W	3000K	470 Lm	345 Lm	102
DO497WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 18V	12W	3000K	940 Lm	609 Lm	182
DO497WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 18V	12W	3000K	940 Lm	609 Lm	182
DO498WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 27V	16W	3000K	1400 Lm	1011 Lm	262
DO498WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 27V	16W	3000K	1400 Lm	1011 Lm	262
DO499WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 36V	20W	3000K	1880 Lm	1217 Lm	342
DO499WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 36V	20W	3000K	1880 Lm	1217 Lm	342




MATT BLACK




MATT WHITE


ACCESSOIRES	DESCRIPTION	L (mm)
CD127	DALI PCU LIGHTING MANAGEMENT	48





 Recessed ceiling mounting only.

 Indoor use only.




 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 0,20 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Beam 45°.


 Product in conformity CE.


 CRI>80


 LED specifications.

 UGR below 19.


 Photobiological risk RG0


 Test on 650°.


 Product can not be covered after installation even with insulation.

 Power supply included.

 The product is dimmable.

 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.