




DUCA


- Adjustable round recessed spotlight.
- Low luminance reflector.
- Beam reducer ring.
- Fastened with springs.
- Remote dimmable converter supplied (DALI versions: converter with push-dim function).





CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
PHASE CUT DIMMABLE									
DO380SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	370 Lm	24°
DO380SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	370 Lm	24°
DO380WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	391 Lm	24°
DO380WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	391 Lm	24°
DO380NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	487 Lm	24°
DO380NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	487 Lm	24°
DO379SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	354 Lm	36°
DO379SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	354 Lm	36°
DO379WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	393 Lm	36°
DO379WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	393 Lm	36°
DO379NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	468 Lm	36°
DO379NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	468 Lm	36°
DALI DIMMABLE									
DO380SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	370 Lm	24°
DO380SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	370 Lm	24°
DO380WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	391 Lm	24°
DO380WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	391 Lm	24°
DO380NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	487 Lm	24°
DO380NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	487 Lm	24°
DO379SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	354 Lm	36°
DO379SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	354 Lm	36°
DO379WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	393 Lm	36°
DO379WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	393 Lm	36°
DO379NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	468 Lm	36°
DO379NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	468 Lm	36°


 Recessed ceiling mounting only.


 Indoor use only.


 Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.

 Protection against an impact energy of 0,20 Joule.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Hole cut to insert luminaire (78mm)

 The luminaire can be adjusted vertically up to a maximum of 30°.

 Horizontal orientation maximum to 355°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 700mA DC.



The product is dimmable.



5 years warranty.



Photometric data available on our website: www.indigo-lighting.com