


EPI RD

RE
2020




- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO466WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 15V	7W	3000K	750 Lm	571 Lm
DO466WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 15V	7W	3000K	750 Lm	571 Lm
DO466NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 150mA 36V	7W	4000K	800 Lm	599 Lm
DO466NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 15V	7W	4000K	800 Lm	599 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (70mm)



Beam 36°.



Product in conformity CE.



CRI>80



LED specifications.



UGR below 19.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.






The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.