TECHNICAL DATA OUTDOOR CEILING LIGHTS




FARO 1

- Wall lamp for outdoor indoor and outdoor lighting.

- Clear tempered glass diffuser.
- With cable inlet and outlet.
- Dimmable converter built in the device.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency E.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
OU447WW05	MATT BLACK	ALUMINIUM	AC 230V	24W	3000K	3150 Lm	2595 Lm
OU447WW30	MATT WHITE	ALUMINIUM	AC 230V	24W	3000K	3150 Lm	2605 Lm
OU447NW05	MATT BLACK	ALUMINIUM	AC 230V	24W	4000K	3200 Lm	2770 Lm
OU447NW30	MATT WHITE	ALUMINIUM	AC 230V	24W	4000K	3200 Lm	2750 Lm





MATT BLACK

MATT WHITE

	Ceiling mounting only.
	Indoor and outdoor use.
IP 65	Protected against the ingress of dust. Protected against jets of water.
IK 06	Protection against an impact energy of 1 Joule.
<u> </u>	Earth wire . Fixture equipped with primary insulation only.
36°	Beam 36°.
CE	Product in conformity CE.
CRI >80	CRI>80
LED L80B20 50.000h	LED specifications.
UGR <19	UGR below 19.
RG1	Photobiological risk RG1
750°	Test on 750°.
	Power supply included.
DIM	The product is dimmable.
5	5 years warranty.
0	Photometric data available on our website: www.indigo-lighting.com

OUTDOOR

CEILING LIGHTS



Replaceable control gear by an electrician.

Replaceable LED light source by an electrician.

