
## TECHNICAL DATA OUTDOOR CEILING LIGHTS



## FARO 2

- Ceiling lamp for indoor and outdoor lighting.
- Clear tempered glass diffuser.
- With cable inlet and outlet.
- Dimmable converter built in the device.
- Compatible with start and end-of-phase dimmer.
- This product contains 1 light source(s) of energy efficiency E.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
OU448WW05	MATT BLACK	ALUMINIUM	AC 230V	34W	3000K	4350 Lm	3760 Lm
OU448WW30	MATT WHITE	ALUMINIUM	AC 230V	34W	3000K	4350 Lm	3865 Lm
OU448NW05	MATT BLACK	ALUMINIUM	AC 230V	34W	4000K	4360 Lm	3940 Lm
OU448NW30	MATT WHITE	ALUMINIUM	AC 230V	34W	4000K	4360 Lm	3785 Lm



MATT BLACK

MATT WHITE

Ceiling mounting only.
Indoor and outdoor use.
Protected against the ingress of dust. Protected against jets of water. 65
Protection against an impact energy of 1 Joule.
$\square$ Earth wire . Fixture equipped with primary insulation only.
Beam 60°.
<b>C E</b> Product in conformity CE.
CRI 280 280
LED specifications.
UGR below 19. <19
RG1 Photobiological risk RG1
<b>750°</b> Test on 750°.
Power supply included.
The product is dimmable.
5 years warranty.
Photometric data available on our website: www.indigo-lighting.com

**OUTDOOR** 

## **CEILING LIGHTS**



Replaceable control gear by an electrician.

Replaceable LED light source by an electrician.

