




















FILI 2 RX-B



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO285WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 300mA 37V	13W	3000K	1180 Lm	791 Lm





BLANC MAT


-  Recessed ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Hole cut to insert luminaire. (80mm)
-  Minimum ceiling height to insert luminaire. (200mm)
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 355°.
-  Beam 40°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Product can not be covered after installation even with insulation.
-  Power supply included.
-  Connect to a constant current Led power supply of 300mA DC.



3 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.