


# FOCEA 1 SX PLUS

- 3 in 1 adjustable rectangular recessed downlight.
- 2700K, 3000K or 4000K as desired via a switch on the converter.
- Protective glass.
- Fastened with springs.
- Remote non-dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO48905	BLACK	CAST ALUMINIUM	AC 230V		40W	2700-3000-4000K	3400 Lm (4000K)	2393 Lm (4000K)
DO48904	WHITE	CAST ALUMINIUM	AC 230V	DC 950mA 36V	40W	2700-3000-4000K	3400 Lm (4000K)	2393 Lm (4000K)



BLACK



WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Rectangular piercing to insert the luminaire. (225x135mm)



Minimum ceiling height to insert luminaire. (160mm)



Vertical orientation maximum to 80°.



Beam 60°.



Product in conformity CE.



CRI>90



3 CCT.



LED specifications.



Test on 650°.



Photobiological risk RG1



Product can not be covered after installation even with insulation.




Power supply included.





Connect to a constant current Led power supply of 950mA DC.



**5** 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.