


FOX 1 R



| CODE | COLOR | MATERIAL | AC | DC | LED | T° (K) | LED Lumen | System Lumen |
|-----------|------------|----------------|---------|--------------|-----|--------|-----------|--------------|
| DO101WW05 | MATT BLACK | CAST ALUMINIUM | AC 230V | DC 350mA 30V | 10W | 3000K | 900 Lm | 600 Lm |
| DO101WW30 | MATT WHITE | CAST ALUMINIUM | AC 230V | DC 350mA 30V | 10W | 3000K | 900 Lm | 600 Lm |
| DO101NW05 | MATT BLACK | CAST ALUMINIUM | AC 230V | DC 350mA 30V | 10W | 4000K | 1030 Lm | 685 Lm |
| DO101NW30 | MATT WHITE | CAST ALUMINIUM | AC 230V | DC 350mA 30V | 10W | 4000K | 1030 Lm | 685 Lm |



NOIR MAT

BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (140 mm)



Beam 110°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation (France).



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.




5 years warranty.






Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.