


FOX 2 RD

RE
2020



- Fixed round recessed downlight.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with end-of-phase dinner.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO102WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 57V	19W	3000K	2700 Lm	1725 Lm
DO102WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 57V	19W	3000K	2700 Lm	1725 Lm
DO102NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 57V	19W	4000K	2800 Lm	1805 Lm
DO102NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 57V	19W	4000K	2800 Lm	1805 Lm



MATT BLACK

MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (210mm)



Beam 110°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.




Connect to a constant current Led power supply of 350mA DC.





The product is dimmable.



5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable LED light source by an electrician.

 Replaceable control gear by an electrician.