




# GARI


- Adjustable round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied (DALI versions: converter with push-dim function).





CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
<b>PHASE CUT DIMMABLE</b>									
DO378SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	408 Lm	24°
DO378SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	408 Lm	24°
DO378WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	420 Lm	24°
DO378WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	420 Lm	24°
DO378NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	469 Lm	24°
DO378NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	469 Lm	24°
DO377SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	423 Lm	36°
DO377SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	423 Lm	36°
DO377WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	449 Lm	36°
DO377WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	449 Lm	36°
DO377NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	519 Lm	36°
DO377NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	519 Lm	36°
<b>DALI DIMMABLE</b>									
DO378SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	408 Lm	24°
DO378SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	408 Lm	24°
DO378WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	420 Lm	24°
DO378WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	420 Lm	24°
DO378NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	469 Lm	24°
DO378NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	469 Lm	24°
DO377SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	423 Lm	36°
DO377SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	423 Lm	36°
DO377WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	449 Lm	36°
DO377WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	449 Lm	36°
DO377NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	519 Lm	36°
DO377NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	519 Lm	36°


 Recessed ceiling mounting only.


 Indoor use only.


 Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.

 Protection against an impact energy of 0,20 Joule.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Hole cut to insert luminaire (78mm)

 The luminaire can be adjusted vertically up to a maximum of 30°.

 Horizontal orientation maximum to 355°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 700mA DC.



The product is dimmable.



5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)