





GL07


This product contains 1 light source(s) of energy efficiency F.





CODE	MATERIAL	AC	LED	T° (K)	System Lumen	α
GL07D24X30	STAINLESS STEEL 316	AC 230V	8,5W	3000K	695 Lm	24°
GL07D24X40	STAINLESS STEEL 316	AC 230V	8,5W	4000K	695 Lm	24°
GL07D38X30	STAINLESS STEEL 316	AC 230V	8,5W	3000K	695 Lm	38°
GL07D38X40	STAINLESS STEEL 316	AC 230V	8,5W	4000K	695 Lm	38°
GL07D60X30	STAINLESS STEEL 316	AC 230V	8,5W	3000K	695 Lm	60°
GL07D60X40	STAINLESS STEEL 316	AC 230V	8,5W	4000K	695 Lm	60°

ACCESSOIRES	DESCRIPTION	
JB5	IP68 PARALLEL CONNECTION BOX WITH GEL	
WC59	IP68 CONNECTOR	


 Recessed floor mounting only.


 Outdoor use.


 Dust-tight. Watertight (immersible).


 Protection against an impact energy of 20 Joules.


 Earth wire . Fixture equipped with primary insulation only.


 Vertical orientation maximum to 20°.


 Product in conformity CE.

 Colour rendering index >80.


 LED specifications.


 Power supply included.

 Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.

 5 years warranty.



 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.