



GL08


This product contains 2 light source(s) of energy efficiency F.





CODE	MATERIAL	AC	LED	T° (K)	System Lumen	α
GL08D24X30	STAINLESS STEEL 316	AC 230V	17W	3000K	1390 Lm	24°
GL08D38X30	STAINLESS STEEL 316	AC 230V	17W	3000K	1390 Lm	38°
GL08D60X30	STAINLESS STEEL 316	AC 230V	17W	3000K	1390 Lm	60°

ACCESSOIRES	DESCRIPTION	
JB5	IP68 PARALLEL CONNECTION BOX WITH GEL	
WC59	IP68 CONNECTOR	


 Recessed floor mounting only.


 Outdoor use.


 IP67 Dust-tight. Watertight (immersible).


 IK10 Protection against an impact energy of 20 Joules.


 Earth wire . Fixture equipped with primary insulation only.


 20° Vertical orientation maximum to 20°.


 CE Product in conformity CE.

 CRI >80 Colour rendering index >80.


 LED L70B10 70.000h LED specifications.


 Power supply included.

 316 Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.

 5 5 years warranty.



 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.