


H2 LITE CSP

This product contains 1 light source(s) of energy efficiency D.

RE
2020



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DLT551500A	MATT WHITE	STEEL+COMPOSITE	AC 230V	4,2W 6W	2700-3000-4000K	675 Lm (4000K) 950 Lm (4000K)	500 Lm (4000K) 700 Lm (4000K)

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	
RB359BLK	MATT BLACK	COMPOSITE	ROUND FINISHING RING 90mm	
RB359BS	BRUSHED STEEL	COMPOSITE	ROUND FINISHING RING 90mm	
RB359CR	CHROME	COMPOSITE	ROUND FINISHING RING 90mm	
RB359MW	MATT WHITE	COMPOSITE	ROUND FINISHING RING 90mm	
RB359PG	GOLD	COMPOSITE	ROUND FINISHING RING 90mm	
RB359SIL	SILVER	COMPOSITE	ROUND FINISHING RING 90mm	
RB359WH	SHINY WHITE	COMPOSITE	ROUND FINISHING RING 90mm	
SQB360BLK	MATT BLACK	COMPOSITE	SQUARE FINISHING RING 90x90mm	
SQB360MW	MATT WHITE	COMPOSITE	SQUARE FINISHING RING 90x90mm	
DLCVT110BLK	MATT BLACK	STEEL	MOUNTING RING 110mm	
DLCVT110BS	BRUSHED STEEL	STEEL	MOUNTING RING 110mm	
DLCVT110MW	MATT WHITE	STEEL	MOUNTING RING 110mm	
DLCVT110WH	SHINY WHITE	STEEL	MOUNTING RING 110mm	

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
DLCONVERT70BS	BRUSHED STEEL	STEEL	MOUNTING RING 170mm
DLCONVERT70CR	CHROME	STEEL	MOUNTING RING 170mm
DLCONVERT70MW	MATT WHITE	STEEL	MOUNTING RING 170mm
DLCONVERT70WH	SHINY WHITE	STEEL	MOUNTING RING 170mm



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm to 72mm)



Beam 55°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.



LED specifications.



In compliance with current thermal regulation (France).



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Power supply included.



The product is dimmable.



7 years warranty.

