


H2 LITE SELECT














This product contains 1 light source(s) of energy efficiency E.






RE
2020



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DL5485500	MATT WHITE	STEEL+COMPOSITE	AC 230V	DC 250mA 18V	5,4W	2700-3000-4000K	625 Lm (4000K)	570 Lm (4000K)

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	
RB359BLK	MATT BLACK	COMPOSITE	ROUND FINISHING RING 90mm	
RB359BS	BRUSHED STEEL	COMPOSITE	ROUND FINISHING RING 90mm	
RB359CR	CHROME	COMPOSITE	ROUND FINISHING RING 90mm	
RB359MW	MATT WHITE	COMPOSITE	ROUND FINISHING RING 90mm	
RB359PG	GOLD	COMPOSITE	ROUND FINISHING RING 90mm	
RB359SIL	SILVER	COMPOSITE	ROUND FINISHING RING 90mm	
RB359WH	SHINY WHITE	COMPOSITE	ROUND FINISHING RING 90mm	
SQB360BLK	MATT BLACK	COMPOSITE	SQUARE FINISHING RING 90x90mm	
SQB360MW	MATT WHITE	COMPOSITE	SQUARE FINISHING RING 90x90mm	
DLCVT110BLK	MATT BLACK	STEEL	MOUNTING RING 110mm	
DLCVT110BS	BRUSHED STEEL	STEEL	MOUNTING RING 110mm	
DLCVT110MW	MATT WHITE	STEEL	MOUNTING RING 110mm	
DLCVT110WH	SHINY WHITE	STEEL	MOUNTING RING 110mm	

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	
DLCONVERT70BS	BRUSHED STEEL	STEEL	MOUNTING RING 170mm	
DLCONVERT70CR	CHROME	STEEL	MOUNTING RING 170mm	
DLCONVERT70MW	MATT WHITE	STEEL	MOUNTING RING 170mm	
DLCONVERT70WH	SHINY WHITE	STEEL	MOUNTING RING 170mm	



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (60mm to 80mm)



Beam 60°.



Product in conformity CE.



Colour rendering index >90.



Selectable colour temperature.



LED specifications.



In compliance with current thermal regulation (France).



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Class II power supply included.




Connect to a constant current Led power supply of 250mA DC.




The product is dimmable.



5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.

