


# H2 PRO EXTREME CSP

This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
H2EXT1B	MATT BLACK	ALU.+COMPOSITE	AC 230V	5W	2200-2700-3000K	600 Lm (3000K)	560 Lm (3000K)
H2EXT1A	ANTHRACITE	ALU.+COMPOSITE	AC 230V	5W	2200-2700-3000K	600 Lm (3000K)	560 Lm (3000K)
H2EXT1W	MATT WHITE	ALU.+COMPOSITE	AC 230V	5W	2200-2700-3000K	600 Lm (3000K)	560 Lm (3000K)



MATT BLACK



ANTHRACITE



MATT WHITE



Recessed ceiling mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (65mm to 75mm)



Beam 40°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.



Photobiological risk RG1



LED specifications.



Test on 650°.



Product can not be covered after installation even with insulation.




Luminaire with a 230V LED module.



The product is dimmable.



4 years warranty.



Replaceable LED light source by an electrician.