


HAPPY 1

- Fixed round ceiling lamp.
- Non-dimmable or dimmable converter built in in the device.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA219WW05	MATT BLACK	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW08	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW23	MATT BLACK - BLACK CHROME	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW30	MATT WHITE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW49	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA219WW22	MATT WHITE - CHROME BLACK	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW05	MATT BLACK	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW08	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW23	MATT BLACK - BLACK CHROME	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW30	MATT WHITE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW49	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm
WA238WW22	MATT WHITE - CHROME BLACK	ALUMINIUM	AC 230V	7W	3000K	600 Lm	435 Lm



MATT BLACK



MATT BLACK - CHAMPAGNE



MATT BLACK - SILVER



MATT BLACK - BLACK CHROME



MATT WHITE




MATT WHITE - CHAMPAGNE





MATT WHITE - SILVER




MATT WHITE - CHROME BLACK

 Ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 2 Joules.

 Earth wire . Fixture equipped with primary insulation only.

 Beam 40°.

 Product in conformity CE.


 CRI>90

 LED specifications.


UGR
<19 UGR below 19.


RG1 Photobiological risk RG1


650° Test on 650°.

 Power supply included.

3 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.