


HAPPY 2

- Fixed round ceiling lamp.
- Non-dimmable or dimmable converter built in in the device.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA220WW05	MATT BLACK	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW08	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW23	MATT BLACK - BLACK CHROME	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW30	MATT WHITE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW49	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA220WW22	MATT WHITE - CHROME BLACK	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW05	MATT BLACK	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW08	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW23	MATT BLACK - BLACK CHROME	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW30	MATT WHITE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW49	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm
WA239WW22	MATT WHITE - CHROME BLACK	ALUMINIUM	AC 230V	13W	3000K	1155 Lm	855 Lm



MATT BLACK



MATT BLACK - CHAMPAGNE



MATT BLACK - SILVER



MATT BLACK - BLACK CHROME



MATT WHITE




MATT WHITE - CHAMPAGNE





MATT WHITE - SILVER





MATT WHITE - CHROME BLACK

 Ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 2 Joules.

 Earth wire . Fixture equipped with primary insulation only.

 Beam 40°.

 Product in conformity CE.


 CRI>90

 LED specifications.


UGR
<19 UGR below 19.


RG1 Photobiological risk RG1


650° Test on 650°.

 Power supply included.

3 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.