


HD1014 R



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
HD1014R25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	760 Lm	655 Lm
HD1014R30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	760 Lm	655 Lm



ALUMINIUM



BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (60mm)



Beam 38°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation (France).



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.




5 years warranty.




Photometric data available on our website: www.indigo-lighting.com





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.