


HELLO 2 D

- Spotlight for diffuse lighting.
- Adapter for Track III SURFACE.
- Dimmable converter built in the device.
- Compatible with end-of-phase dinner.
- Reserve a specific phase of the track for the dimmable products.

This product contains 1 light source(s) of energy efficiency F.





















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR390WW05	MATT BLACK	ALUMINIUM	AC 230V	17W	3000K	2160 Lm	1740 Lm
TR390WW30	MATT WHITE	ALUMINIUM	AC 230V	17W	3000K	2160 Lm	1740 Lm




MATT BLACK

MATT WHITE

-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,70 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 350°.
-  Beam 100°.
-  Product in conformity CE.
-  CRI>80
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  The product is dimmable.
-  3 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.