SUSPENSIONS



System Lumen

1835 Lm

1835 Lm

HELLO 2 P


- Decorative hanging lamp.
- PMMA diffuser.
- Supplied with black or white textile power cable (adjustable up to 2.00m max).
- Dimmable converter built in in the base.

COLOR

- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.

MATERIAL



LED Lumen

2160 Lm

2160 Lm

SU167WW05	MATT BLACK	ALUMINIUM	AC 230V	18W	3000K	
SU167WW30	MATT WHITE	ALUMINIUM	AC 230V	18W	3000K	
"						

AC

LED

T° (K)





CODE

Suspended mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids



Protection against an impact energy of 0,70 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Beam 110°.



Product in conformity CE.



CRI CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.



The product is dimmable.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.