


# IENA RDX-230

RE  
2020



- 4 in 1 adjustable round recessed spotlight.
- 2700K, 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Can be covered with peeled or blown insulation.
- Automatic double terminal block.
- Does not require a converter.
- Dimmable.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO44605	MATT BLACK	ALU.+COMPOSITE	AC 230V	5W	2700-3000-4000-6000K	620 Lm (4000K)	506 Lm (4000K)
DO44630	MATT WHITE	ALU.+COMPOSITE	AC 230V	5W	2700-3000-4000-6000K	620 Lm (4000K)	506 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 60°.



Product in conformity CE.



CRI>80



4 CCT.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 850°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Luminaire with a 230V LED module.






The product is dimmable.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.