


IPHO 82 SD

- Fixed square recessed spotlight.
- Fastened with springs.
- Automatic double terminal block.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency E.



RE
2020



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO16505	BLACK	GLASS	AC 230V	DC 500mA 18V	9W	3000K	900 Lm	620 Lm
DO16530	WHITE	GLASS	AC 230V	DC 500mA 18V	9W	3000K	900 Lm	705 Lm



BLACK



WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (60mm)



Beam 38°.



Product in conformity CE.



CRI>80



LED specifications.



UGR below 19.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 500mA DC.






The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.