

IRO 2

- Hanging fixture for 48V track.
- Supplied with adjustable 1.50m cable .

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
NOT DIMMABLE							
TR312SW05	MATT BLACK	ALUMINIUM	DC 48V	19W	2700K	1850 Lm	1200 Lm
TR312WW05	MATT BLACK	ALUMINIUM	DC 48V	19W	3000K	2050 Lm	1215 Lm
TR312NW05	MATT BLACK	ALUMINIUM	DC 48V	19W	4000K	2270 Lm	1651 Lm
DALI DIMMABLE							
TR312WW05DA	MATT BLACK	ALUMINIUM	DC 48V	19W	3000K	2050 Lm	1215 Lm
TR312NW05DA	MATT BLACK	ALUMINIUM	DC 48V	19W	4000K	2270 Lm	1651 Lm

Suspended mounting only.

Indoor use only.

Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

Protection against an impact energy of 0,20 Joule.

Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

Beam 50°.

Product in conformity CE.

CRI>80

LED specifications.

Photobiological risk RG1

Test on 650°.

Connect to a constant voltage LED power supply of 48VDC.

3 years warranty.

Photometric data available on our website: www.indigo-lighting.com

Replaceable LED light source by an electrician.