


# IZA 2 SDX

- 2 in 1 adjustable rectangular recessed downlight.
- 3000K or 4000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Remote dimmable converters supplied.
- Compatible with start and end-of-phase dimmer.



This product contains 2 light source(s) of energy efficiency G.

| CODE    | COLOR      | MATERIAL  | AC      | DC             | LED   | T° (K)     | LED Lumen         | System Lumen      |
|---------|------------|-----------|---------|----------------|-------|------------|-------------------|-------------------|
| DO53205 | MATT BLACK | ALUMINIUM | AC 230V | 2xDC 600mA 36V | 2x24W | 3000-4000K | 2x2100 Lm (4000K) | 2x1790 Lm (4000K) |
| DO53230 | MATT WHITE | ALUMINIUM | AC 230V | 2xDC 600mA 36V | 2x24W | 3000-4000K | 2x2100 Lm (4000K) | 2x1790 Lm (4000K) |



MATT BLACK

MATT WHITE

- Recessed ceiling mounting only.
- Indoor use only.
- Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
- Protection against an impact energy of 0,70 Joule.
- Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
- Rectangular piercing to insert the luminaire. (300x162mm)
- Minimum ceiling height to insert luminaire. (150mm)
- The luminaire can be adjusted vertically up to a maximum of 30° in both directions.
- Beam 60°.
- Product in conformity CE.
- CRI>80
- 2 CCT.
- LED specifications.
- Photobiological risk RG1
- Test on 650°.
- Product can not be covered after installation even with insulation.
- Power supply included.

600  
mA

Connect to a constant current Led power supply of 600mA DC.




The product is dimmable.

5


5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.