

# JACK 3 TP
















- Decorative hanging fixture.
- Adapter for Track III SURFACE.
- Supplied with textile power cable (adjustable 1.60m max)  
Colour 05 - 13 - 06 : black cable.  
Colour 30 - 28 - 02 - white cable.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Dimmable converter built in the device.
- Compatible with end-of-phase dimmer.
- Reserve a specific phase of the track for the dimmable products.



This product contains 1 light source(s) of energy efficiency F.


CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR42605	MATT BLACK	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)
TR42613	MATT BLACK - BRASS	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)
TR42606	MATT BLACK - ROSE GOLD	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)
TR42630	MATT WHITE	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)
TR42628	MATT WHITE - BRASS	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)
TR42602	MATT WHITE - ROSE GOLD	ALUMINIUM	AC 230V	25W	2700-3000-4000K	2810 Lm (4000K)	2270 Lm (4000K)




-  Suspended mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 60°.
-  Product in conformity CE.
-  CRI>90
-  3 CCT.  
2700K  
3000K  
4000K
-  LED specifications.  
L80B10  
50.000h
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.
-  The product is dimmable.
-  5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.