


















JACK T




CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR41613	MATT BLACK - BRASS	ALUMINIUM	AC 230V	10W	2700-3000-4000K	1120 Lm (4000K)	795 Lm (4000K)
TR41628	MATT WHITE - BRASS	ALUMINIUM	AC 230V	10W	2700-3000-4000K	1120 Lm (4000K)	865 Lm (4000K)




NOIR MAT - LAITON BLANC MAT - LAITON

-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 350°.
-  Beam 38°.
-  Product in conformity CE.
-  Colour rendering index >90.
-  Selectable colour temperature.
2700 K
3000 K
4000 K
-  LED specifications.
L80B10
50.000h
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.