


JADE RDX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- As an option, DALI CD140 dimmable converter to be ordered separately.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO272WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	12W	3000K	1400 Lm	1000 Lm
DO272WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	12W	3000K	1400 Lm	1000 Lm
DO272NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	12W	4000K	1450 Lm	1030 Lm
DO272NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	12W	4000K	1450 Lm	1030 Lm



MATT BLACK



MATT WHITE

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD140	3-18W	AC 230V	DC 350mA	1	1	80°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,50 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (96mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 38°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.





Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.