


# JUNE 1 C

- Decorative wall or ceiling lamp.
- Opaline PS diffuser.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- Dimmable conveter built in the device.
- Compatible with start and end-of-phase dimmer.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA22205	MATT BLACK	ALUMINIUM	AC 230V	18W	2700-3000-4000K	3300 Lm (4000K)	1775 Lm (4000K)
WA22230	MATT WHITE	ALUMINIUM	AC 230V	18W	2700-3000-4000K	3300 Lm (4000K)	1775 Lm (4000K)



MATT BLACK



MATT WHITE



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Beam 120°.



Product in conformity CE.



CRI>80



3 CCT.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




The product is dimmable.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.