


# KACI R-B

- Round recessed spotlight.
- Etched glass diffuser.
- Fastened with louvers.
- Prewired 0.50m.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Remote non-dimmable converter supplied, can be placed at max. 10m from the device.
- Accessory for exposed installation to be ordered separately.

This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
KC211R25	BRUSHED ALUMINIUM	ALUMINIUM	AC 230V	DC 12V	3W	3000K	350 Lm	220 Lm
KC211R30	MATT WHITE	ALUMINIUM	AC 230V	DC 12V	3W	3000K	350 Lm	220 Lm



BRUSHED ALUMINIUM

MATT WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
BASEKC211R25	BRUSHED ALUMINIUM	ALUMINIUM	KACI R-B BASE ROUND 
BASEKC211R30	MATT WHITE	ALUMINIUM	KACI R-B BASE ROUND 



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (55 mm)



Beam 100°.



Product in conformity CE.



CRI >80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



12V  
DC


Connect to a constant voltage LED power supply of 12VDC.

5


5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.