


# KACI S-B



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
KC211S25	BRUSHED ALUMINIUM	ALUMINIUM	AC 230V	DC 12V	3W	3000K	350 Lm	220 Lm
KC211S30	MATT WHITE	ALUMINIUM	AC 230V	DC 12V	3W	3000K	350 Lm	220 Lm



ALUMINIUM BROSSE

BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (55 mm)



Beam 100°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)




Connect to a constant voltage LED power supply of 12VDC.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.