




KALA


- Square terminal with solar cells and rechargeable battery.
- Works only when the luminosity is less than 20 Lux.
- With 120° IR sensor and switch, detection radius 6m max.
- Two levels of lightin after detection, 225 lumens for 45 seconds then 35 lumens with autonomy of 15 hours.
- Charing time 6 to 8 hours in full sunlight.
- Stake to be buried included.





This product contains 1 light source(s) of energy efficiency B.


CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
OU342NW24	ANTHRACITE	CAST ALUMINIUM	DC 3,7V	2W	4000K	600 Lm	225 Lm


ACCESSOIRES	DESCRIPTION
OU445	REPLACEMENT BATTERY 
OU468	REPLACEMENT GROUND SPIKE 


 Floor mounting only.

 Outdoor use.


 Protected against dust, And protected against water spray.


 Protection against an impact energy of 0,70 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Product in conformity CE.


 CRI>80


 LED specifications.


 Photobiological risk RG1

 Test on 650°.

 With solar cells.

 With sensor.

 3 years warranty.

 Replaceable LED light source by an electrician.