


KALI R-230 B

- Round recessed spotlight.
- Opaline glass diffuser.
- Fastened with louvers.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Does not require a converter.
- Non dimmable.
- Accessory for exposed installation to be ordered separately.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO337WW05	MATT BLACK	ALUMINIUM	AC 230V	5W	3000K	410 Lm	280 Lm
DO337WW21	SATIN NICKEL	ALUMINIUM	AC 230V	5W	3000K	410 Lm	280 Lm
DO337WW30	MATT WHITE	ALUMINIUM	AC 230V	5W	3000K	410 Lm	280 Lm






MATT BLACK



SATIN NICKEL



MATT WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	
DO33805	MATT BLACK	ALUMINIUM	KALI R-230 B ROUND BASE	 20
DO33821	SATIN NICKEL	ALUMINIUM	KALI R-230 B ROUND BASE	 20
DO33830	MATT WHITE	ALUMINIUM	KALI R-230 B ROUND BASE	 20



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (55 mm)



Beam 100°.



Product in conformity CE.



CRI >80



LED specifications.



Photobiological risk RG1



Test on 650°.





Product can be covered after installation with insulation. (not blown)




Luminaire with a 230V LED module.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.